

Revision Date 04-Jan-2016

SAFETY DATA SHEET

Version 2

1. IDENTIFICATION

Product identifier Product Name	ULTRA BLACK GASKET MAKER 3.35OZ		
Other means of identification Product Code	82180		
Synonyms	None		
Recommended use of the chemical	and restrictions on use		
Recommended Use	Sealant		
Uses advised against	No information available		
Details of the supplier of the safety	data sheet		
Manufacturer Address	<u>Distributor</u>		
ITW Permatex	ITW Permatex Canada		
6875 Parkland Blvd.	35 Brownridge Road, Unit 1		
Solon, OH 44139 USA	Halton Hills, ON Canada L7G 0C6		
	Telephone: (800) 924-6994		
Company Phone Number	1-87-Permatex		
	(877) 376-2839		
24 Hour Emergency Phone Number	Chem-Tel: 800-255-3924		
0,	International Emergency:		
	00+1+ 813-248-0585		
	Contract Number: MIS0003453		
E-mail address	mail@permatex.com		

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.


Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview

Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity

25.95 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

CAS No	Weight-%	Trade Secret
70131-67-8	15 - 40	*
471-34-1	15 - 40	*
1317-65-3	10 - 30	*
2224-33-1	3 - 7	*
64742-47-8	3 - 7	*
96-29-7	1 - 5	*
1333-86-4	0.1 - 1	*
	70131-67-8 471-34-1 1317-65-3 2224-33-1 64742-47-8 96-29-7	70131-67-8 15 - 40 471-34-1 15 - 40 1317-65-3 10 - 30 2224-33-1 3 - 7 64742-47-8 3 - 7 96-29-7 1 - 5

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Description of first and measures				
General advice	Get medical advice/attention if you feel unwell.			
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.			
Skin contact	IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.			
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.			
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.			
Self-protection of the first aider	Use personal protective equipment as required.			
Most important symptoms and effect	cts, both acute and delayed			
Symptoms	Symptoms See section 2 for more information.			
Indication of any immediate medical	I attention and special treatment needed			
Note to physicians Treat symptomatically.				
5. FIRE-FIGHTING MEASURES				
<u>Suitable extinguishing media</u> Carbon dioxide (CO2), Dry chemical, Foam				
<u>Unsuitable extinguishing media</u> None.				
Specific hazards arising from the chemical None in particular.				
Explosion dataSensitivity to Mechanical ImpactNone.Sensitivity to Static DischargeNone.				
Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.				
6. ACCIDENTAL RELEASE MEASURES				

Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.	
Environmental precautions		
Environmental precautions	Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological Information.	
Methods and material for containment and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.	

Methods for cleaning up	Ensure adequate ventilation. Flood with water to complete polymerization and scrape off floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if walked on.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.		
Conditions for safe storage, including any incompatibilities			
Storage Conditions	Keep container tightly closed in a dry and well-ventilated place. Protect from moisture.		
Incompatible materials	Strong oxidizing agents, Acids, Water		
8. EXPOSURE CONTROLS/PERSONAL PROTECTION			

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE	-	-	TWA: 10 mg/m ³ total dust
471-34-1			TWA: 5 mg/m ³ respirable dust
LIMESTONE	-	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust
1317-65-3		TWA: 5 mg/m ³ respirable fraction	TWA: 5 mg/m ³ respirable dust
		(vacated) TWA: 15 mg/m ³ total dust	
		(vacated) TWA: 5 mg/m ³ respirable	
		fraction	
CARBON BLACK	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	-	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m ³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Skin and body protection	Wear protective gloves and protective clothing.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Paste Black	
Appearance Odor	Mild	
Odor threshold	No information available	
Property	Values	Remarks • Method
рН	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	Not Applicable	Polymerization
Flash point	> 93 °C / > 200 °F	Tag Closed Cup
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	<5 mm Hg @ 80°F	
Vapor density	>1	Air = 1
Relative density	1.44	
Water solubility	Not applicable	Polymerization
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other Information		
Softening point Molecular weight	No information available No information available	
VOC Content (%)	3%	
Density	No information available	
Bulk density	No information available	
Buik delibity		

10. STABILITY AND REACTIVITY

Reactivity No data available

<u>Chemical stability</u> Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid Excessive heat.

Excessive neal.

Incompatible materials Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products

Carbon oxides Nitrogen oxides (NOx) Formaldehyde May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	-	> 16 mL/kg (Rabbit)	> 8750 mg/m³(Rat)7 h
CALCIUM CARBONATE 471-34-1	= 6450 mg/kg (Rat)	-	-
SYNTHETIC ISOPARAFFINIC HYDROCARON 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
2-BUTANONE OXIME 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat)4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity	No informatic No informatic The table bel	on available.	h agency has listed any ing	gredient as a carcinogen.
Chemical Name	ACGIH	IARC	NTP	OSHA
CARBON BLACK 1333-86-4	A3	Group 2B	-	Х
ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present				
Target Organ Effects Eyes, Respiratory system, Skin.				
The following values are ATEmix (oral) ATEmix (dermal)	calculated based on cha 12170 mg/kg 10754 mg/kg)	ument .	

12. ECOLOGICAL INFORMATION

Ecotoxicity

93.91 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
SYNTHETIC ISOPARAFFINIC	-	45: 96 h Pimephales promelas mg/L	4720: 96 h Den-dronereides
HYDROCARON		LC50 flow-through 2.2: 96 h	heteropoda mg/L LC50
64742-47-8		Lepomis macrochirus mg/L LC50	
		static 2.4: 96 h Oncorhynchus	
		mykiss mg/L LC50 static	
2-BUTANONE OXIME	83: 72 h Desmodesmus subspicatus	777 - 914: 96 h Pimephales	750: 48 h Daphnia magna mg/L
96-29-7	mg/L EC50	promelas mg/L LC50 flow-through	EC50
	_	760: 96 h Poecilia reticulata mg/L	
		LC50 static 320 - 1000: 96 h	
		Leuciscus idus mg/L LC50 static	

		-	
CARBON BLACK	-	-	5600: 24 h Daphnia magna mg/L
1333-86-4			ÉC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

<u>Mobility</u>

No information available.

Chemical Name	Partition coefficient	
2-BUTANONE OXIME	0.65	
96-29-7		

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	Not applicable

14. TRANSPORT INFORMATION

DOT Proper shipping name:	Not regulated
IATA Proper shipping name:	Not regulated
IMDG Proper shipping name:	Not regulated

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Not Listed.
ENCS	Not Listed.
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
CARBON BLACK - 1333-86-4	Carcinogen	
SILICA, QUARTZ - 14808-60-7	Carcinogen	
ETHANOL - 64-17-5	Carcinogen	
	Developmental	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
LIMESTONE 1317-65-3	Х	X	Х
ALUMINIUM POWDER 7429-90-5	X	X	Х
CARBON BLACK 1333-86-4	Х	X	Х
SILICA, QUARTZ 14808-60-7	Х	X	Х
ETHANOL 64-17-5	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u> HMIS

- Health hazards 2 Health hazards 2
- Flammability 1 Flammability 1

Instability 0 Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 04-Jan-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet