SAFETY DATA SHEET

Category 1

Category 1

Revision Date 12-Jun-2015

Г

Version 1

	I. IDENTIFICATION	4
Product identifier Product Name	Gray	
Other means of identification Product Code UN/ID no. SKU(s)	TP2700SP UN1950 None	
Recommended use of the chemi Recommended Use Uses advised against	<u>cal and restrictions on use</u> No information available. No information available	
Details of the supplier of the safe Supplier Address TISCO PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749	<u>≱ty data sheet</u>	
Emergency telephone number Emergency Telephone	Chemtrec 1-800-424-9300	
	2. HAZARDS IDENTIFIC	ATION
Classification OSHA Regulatory Status This chemical is considered hazard	dous by the 2012 OSHA Hazard Communic	cation Standard (29 CFR 1910.1200)
Serious eye damage/eye irritation		Category 2
Germ cell mutagenicity		Category 1B
Carcinogenicity		Category 1A
Specific target organ toxicity (single		Category 3
Specific target organ toxicity (repeated exposure)		Category 1

Emergency Overview

Danger

Hazard statements

Aspiration toxicity

Flammable aerosols

Causes serious eye irritation May cause genetic defects May cause cancer May cause drowsiness or dizziness Causes damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Extremely flammable aerosol



Appearance No information available

Physical state Aerosol

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

Harmful to aquatic life with long lasting effects

• Harmful to aquatic life Unknown acute toxicity

17.76% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	10 - 30	*
Propane	74-98-6	10 - 30	*
Talc (powder)	14807-96-6	10 - 30	*
Butane	106-97-8	7 - 13	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	5 - 10	*
Stoddard Solvent	8052-41-3	1 - 5	*
Titanium dioxide	13463-67-7	1 - 5	*
Zinc oxide, as Zn (fume)	1314-13-2	0.1 - 1	*
Ethyl Benzene	100-41-4	0.1 - 1	*

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.	
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician. If symptoms persist, call a physician.	
Skin Contact	Wash off immediately with plenty of water. Call a physician immediately. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.	
Inhalation	Immediate medical attention is required. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately. Move to fresh air in case of accidental inhalation of vapors.	
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Clean mouth with water and drink afterwards plenty of water. Call a physician.	
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.	
Most important symptoms and effects, both acute and delayed		
Symptoms	No information available.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautionsRemove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate
ventilation, especially in confined areas. Use personal protective equipment as required.
Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.
Methods and material for containme	ent and cleaning up
Methods for containment	Prevent further leakage or spillage if safe to do so. Cover powder spill with plastic sheet or tarp to minimize spreading. Dike far ahead of liquid spill for later disposal.
Methods for cleaning up	Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.
Conditions for safe storage, includ	ing any incompatibilities

Storage Conditions	Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep
	containers tightly closed in a cool, well-ventilated place.

Incompatible materials Strong acids. Strong oxidizing agents. Chlorinated compounds.

.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content	TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
Talc (powder)	TWA: 2 mg/m ³ particulate matter	(vacated) TWA: 2 mg/m ³ respirable	IDLH: 1000 mg/m ³
14807-96-6	containing no asbestos and <1%	dust <1% Crystalline silica,	TWA: 2 mg/m ³ containing no
	crystalline silica, respirable fraction	containing no Asbestos	Asbestos and <1% Quartz
		TWA: 20 mppcf if 1% Quartz or	respirable dust
		more, use Quartz limit	
Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³

Stoddard Solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³
8052-41-3		TWA: 2900 mg/m ³	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m ³
		(vacated) TWA: 525 mg/m ³	-
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7	_	(vacated) TWA: 10 mg/m ³ total dust	-
Zinc oxide, as Zn (fume)	STEL: 10 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume	IDLH: 500 mg/m ³
1314-13-2	TWA: 2 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust	Ceiling: 15 mg/m ³ dust
		TWA: 5 mg/m ³ respirable fraction	TWA: 5 mg/m ³ dust and fume
		(vacated) TWA: 5 mg/m ³ fume	STEL: 10 mg/m ³ fume
		(vacated) TWA: 10 mg/m ³ total dust	
		(vacated) TWA: 5 mg/m ³ respirable	
		fraction	
		(vacated) STEL: 10 mg/m ³ fume	
Ethyl Benzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations
	Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles. Face protection shield.
Skin and body protection	No special technical protective measures are necessary.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	Aerosol No information available No information available	Odor Odor threshold	No information available No information available
Property pH Melting point/freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit:	ValuesNo information availableNo information available>= -42 °C / -44 °F-104 °C / -155 °FNo information availableNo information availableNo information availableNo information availableNo information availableNo information available	<u>Remarks • Method</u>	

Vapor pressure	No information
Vapor density	No information
Specific Gravity	0.82
Water solubility	No information
Solubility in other solvents	No information
Partition coefficient	No information
Autoignition temperature	No information
Decomposition temperature	No information
Kinematic viscosity	No information
Dynamic viscosity	No information
Explosive properties	No information
Oxidizing properties	No information
Other Information	
Softening point	No information
Molecular weight	No information
VOC Content (%)	No information
Density	6.80 lbs/gal
Bulk density	No information
Percent solids by weight	29.1%
Percent volatile by weight	44.7%
Percent solids by volume	13.2%
Actual VOC (lbs/gal)	3
Actual VOC (grams/liter)	363.9
FPA VOC (lbs/gal)	42

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	6.80 lbs/gal
Bulk density	No information available
Percent solids by weight	29.1%
Percent volatile by weight	44.7%
Percent solids by volume	13.2%
Actual VOC (lbs/gal)	3
Actual VOC (grams/liter)	363.9
EPA VOC (lbs/gal)	4.2
EPA VOC (grams/liter)	498.3
EPA VOC (lb/gal solids)	22.9

10. STABILITY AND REACTIVITY

available available

available available available available available available available available available

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg(Rat)	-	= 50100 mg/m³(Rat)8 h
Propane 74-98-6	-	-	= 658 mg/L (Rat)4 h
Butane 106-97-8	-	-	= 658 g/m³ (Rat)4 h
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Zinc oxide, as Zn (fume) 1314-13-2	> 5000 mg/kg (Rat)	-	-
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information			
Germ cell mutagenicity Carcinogenicity	No information available. No information available.			
Chemical Name	ACGIH	IARC	NTP	OSHA
Talc (powder) 14807-96-6	-	Group 3	_	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	Х
Group 2B - Possibly Card Group 3 - Not classifiable	as a human carcinogen	tion of the US Department o	f Labor)	
STOT - single exposure STOT - repeated exposure Chronic toxicity	AT - single exposure No information available. AT - repeated exposure No information available.			
Target Organ Effects	s Central nervous system, Central Vascular System (CVS), Eyes, kidney, lungs, Respiratory system, Skin.			
Aspiration hazard	No information	on available.		

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

47.65% of the mixture consists of	components(s) of unknown	hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea

Acetone	-	4.74 - 6.33: 96 h Oncorhynchus	10294 - 17704: 48 h Daphnia
67-64-1		mykiss mL/L LC50 6210 - 8120: 96	magna mg/L EC50 Static 12600 -
		h Pimephales promelas mg/L LC50	12700: 48 h Daphnia magna mg/L
		static 8300: 96 h Lepomis	EC50
		macrochirus mg/L LC50	
Talc (powder)	-	100: 96 h Brachydanio rerio g/L	-
14807-96-6		LC50 semi-static	
Solvent Naphtha, Medium Aliphatic	450: 96 h Pseudokirchneriella	800: 96 h Pimephales promelas	100: 48 h Daphnia magna mg/L
64742-88-7	subcapitata mg/L EC50	mg/L LC50 static	EC50
Ethyl Benzene	4.6: 72 h Pseudokirchneriella	11.0 - 18.0: 96 h Oncorhynchus	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 438: 96 h	mykiss mg/L LC50 static 4.2: 96 h	EĊ50
	Pseudokirchneriella subcapitata	Oncorhynchus mykiss mg/L LC50	
	mg/L EC50 2.6 - 11.3: 72 h	semi-static 7.55 - 11: 96 h	
	Pseudokirchneriella subcapitata	Pimephales promelas mg/L LC50	
	mg/L EC50 static 1.7 - 7.6: 96 h	flow-through 32: 96 h Lepomis	
	Pseudokirchneriella subcapitata	macrochirus mg/L LC50 static 9.1 -	
	mg/L EC50 static	15.6: 96 h Pimephales promelas	
	-	mg/L LC50 static 9.6: 96 h Poecilia	
		reticulata mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Acetone 67-64-1	-0.24
Propane 74-98-6	2.3
Butane 106-97-8	2.89
Ethyl Benzene 100-41-4	3.118

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U002 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1	-	Included in waste stream: F039	-	U002
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Zinc oxide, as Zn (fume) 1314-13-2	Тохіс
Ethyl Benzene 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT UN/ID no. Proper shipping name Hazard Class Description Emergency Response Guide Number	UN1950 Aerosols 2.1 UN1950, Aerosols, 2.1, 126
<u>TDG</u> UN/ID no. Proper shipping name Hazard Class Description	UN1950 Aerosols 2.1 UN1950, Aerosols, 2.1
<u>MEX</u> UN/ID no. Proper shipping name Hazard Class Description	UN1950 Aerosols 2 UN1950, Aerosols, 2
ICAO (air) UN/ID no. Proper shipping name Hazard Class Special Provisions Description	UN1950 Aerosols 2.1 A145, A167 UN1950, Aerosols, 2.1
IATA UN/ID no. Proper shipping name Hazard Class ERG Code Special Provisions Description	UN1950 Aerosols, flammable 2.1 2L A145, A167, A98, A802 UN1950, Aerosols, flammable, 2.1
IMDG UN/ID no. Proper shipping name Hazard Class EmS-No. Special Provisions Description	UN1950 Aerosols 2 F-D, S-U 63,190, 277, 327, 344, 959 UN1950, Aerosols, 2
<u>RID</u> UN/ID no. Proper shipping name Hazard Class Classification code Description	UN1950 Aerosols 2.1 5A UN1950, Aerosols, 2.1
ADR UN/ID no. Proper shipping name Hazard Class Classification code Tunnel restriction code Special Provisions Description	UN1950 Aerosols 2.1 5F (D) 190, 327, 344, 625 UN1950, Aerosols, 2.1, (D)

ADN

Proper shipping name	Aerosols
Hazard Class	2.1
Classification code	5F
Special Provisions	190, 327, 344, 625
Description	UN1950, Aerosols, 2.1
Hazard label(s)	2.1
Limited quantity (LQ)	1 L
Ventilation	VE01, VE04

2.1

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies *
EINECS/ELINCS	Complies *
ENCS	Does not comply *
IECSC	Complies *
KECL	Complies *
PICCS	Does not comply *
AICS	Does not comply *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %		
Ethyl Benzene - 100-41-4	0.1		

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc oxide, as Zn (fume) 1314-13-2	-	Х	-	-
Ethyl Benzene 100-41-4	1000 lb	Х	Х	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
Ethyl Benzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Titanium dioxide - 13463-67-7	Carcinogen	
Ethyl Benzene - 100-41-4	Carcinogen	
Carbon Black - 1333-86-4	Carcinogen	
Crystalline Silica - 14808-60-7	Carcinogen	
	·	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	Х
Propane 74-98-6	Х	Х	Х
Talc (powder) 14807-96-6	Х	Х	Х
Butane 106-97-8	Х	Х	Х
Solvent Naphtha, Medium Aliphatic 64742-88-7	Х	-	-
Stoddard Solvent 8052-41-3	Х	Х	Х
Titanium dioxide 13463-67-7	Х	X	Х
Ethylene Glycol Butyl Ether 111-76-2	Х	X	Х
Xylene 1330-20-7	Х	X	Х
Propylene Glycol Methyl Ether 107-98-2	Х	X	Х
Ethyl Benzene 100-41-4	Х	X	Х
Cobalt 2-ethylhexanoate 136-52-7	Х	-	Х
Diethylene Glycol Methyl Ether 111-77-3	Х	X	Х
Crystalline Silica 14808-60-7	Х	X	Х
Diethylene Glycol Butyl Ether 112-34-5	Х	-	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

This product contains no reportable Hazardous Air Pollutants

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION	1

<u>NFPA</u>	Health hazards 2	Flammability 4	Instability 0	Physical and Chemical Properties *
HMIS	Health hazards 2*	Flammability 4	Physical hazards 0	Personal protection X

Chronic Hazard Star Legend

* = Chronic Health Hazard

Revision Date

12-Jun-2015

Revision Note No information available Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet