# SAFETY DATA SHEET

Revision Date 19-Jun-2015 Version 1

# 1. IDENTIFICATION

Product identifier

**Product Name** CASE POWER TAN LF

Other means of identification

**Product Code** TP275SP UN/ID no. UN1950 SKU(s) None

Recommended use of the chemical and restrictions on use Recommended Use No information available. Uses advised against No information available

Details of the supplier of the safety data sheet

**Supplier Address** 

TISCO

PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

#### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable aerosols	Category 1

### **Emergency Overview**

# Danger

#### Hazard statements

Causes serious eye irritation

May cause genetic defects

May cause cancer

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol

\_\_\_\_



Appearance No information available

Physical state Aerosol

Odor No information available

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

#### Other Information

Causes mild skin irritation

Unknown acute toxicity

7.74% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	15 - 40	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	10 - 30	*
Propane	74-98-6	7 - 13	*
Butane	106-97-8	5 - 10	*
Stoddard Solvent	8052-41-3	1 - 5	*
Titanium dioxide	13463-67-7	1 - 5	*
Ethylene Glycol Butyl Ether	111-76-2	1 - 5	*
Ethyl Benzene	100-41-4	0.1 - 1	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

# **Description of first aid measures**

Revision Date 19-Jun-2015

\_\_\_\_\_

General advice Immediate medical attention is required. In case of accident or unwellness, seek medical

advice immediately (show directions for use or safety data sheet if possible). If symptoms

persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and

upper eyelids. Consult a physician. If symptoms persist, call a physician.

**Skin Contact** Wash off immediately with plenty of water. Call a physician immediately. Wash off

immediately with soap and plenty of water while removing all contaminated clothes and

shoes. If skin irritation persists, call a physician.

Inhalation Immediate medical attention is required. Remove to fresh air. Avoid direct contact with skin.

Use barrier to give mouth-to-mouth resuscitation. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately. Move to fresh air in case of

accidental inhalation of vapors.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Clean mouth

with water and drink afterwards plenty of water. Call a physician.

**Self-protection of the first aider** Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

### 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

No information available.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Use personal protective equipment as required.

Keep people away from and upwind of spill/leak.

**Environmental precautions** 

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

#### Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Cover powder spill with plastic sheet or

tarp to minimize spreading. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust). Pick up and transfer to properly labeled containers. Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent

material.

### 7. HANDLING AND STORAGE

# **Precautions for safe handling**

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Use with local exhaust ventilation. Use

personal protective equipment as required. Do not breathe

dust/fume/gas/mist/vapors/spray. Avoid breathing vapors or mists. Contents under

pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into

opening on top of can.

### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep

containers tightly closed in a cool, well-ventilated place.

Incompatible materials Strong acids. Strong oxidizing agents. Chlorinated compounds.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	IDLH: 2500 ppm
67-64-1	67-64-1 TWA: 250 ppm		TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	
		(vacated) STEL: 2400 mg/m³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content	TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	
Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1900 mg/m <sup>3</sup>
Stoddard Solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) TWA: 525 mg/m <sup>3</sup>	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7		(vacated) TWA: 10 mg/m³ total dust	
Ethylene Glycol Butyl Ether	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m <sup>3</sup>	TWA: 5 ppm
		(vacated) TWA: 25 ppm	TWA: 24 mg/m <sup>3</sup>
		(vacated) TWA: 120 mg/m <sup>3</sup>	
		(vacated) S*	
		S*	

Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
		(vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	STEL: 125 ppm STEL: 545 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles. Face protection shield.

**Skin and body protection** No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state Aerosol

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

Property Values Remarks • Method

pH No information available
Melting point/freezing point
Boiling point / boiling range
Flash point

No information available
No information available
>= -42 °C / -43 °F
-104 °C / -156 °F

Flash point -104 °C / -156 °F
Evaporation rate No information available
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific Gravity 0.80

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available Autoignition temperature No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available Oxidizing properties No information available

#### **TP275SP CASE POWER TAN LF**

#### Other Information

Softening pointNo information availableMolecular weightNo information availableVOC Content (%)No information available

**Density** 6.15 lbs/gal

Bulk density No information available

Percent solids by weight 24.6% Percent volatile by weight 41.0% Percent solids by volume 13.8% Actual VOC (lbs/gal) 2.7 Actual VOC (grams/liter) 328.8 EPA VOC (lbs/gal) 4.2 EPA VOC (grams/liter) 505.1 EPA VOC (lb/gal solids) 19.9

# 10. STABILITY AND REACTIVITY

### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

### **Possibility of Hazardous Reactions**

None under normal processing.

# **Conditions to avoid**

Heat, flames and sparks.

#### Incompatible materials

Strong acids. Strong oxidizing agents. Chlorinated compounds.

# **Hazardous Decomposition Products**

Carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Product Information No data available

**Inhalation** No data available.

**Eye contact** No data available.

**Skin Contact** No data available.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ ( Rat ) 8 h
Solvent Naphtha, Medium Aliphatic > 5000 mg/kg ( Rat ) 64742-88-7		= 3000 mg/kg(Rabbit)	> 5.28 mg/L (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Butane - 106-97-8		-	= 658 g/m³ (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Ethylene Glycol Butyl Ether 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg(Rabbit)	= 450 ppm (Rat) 4 h

\_\_\_\_

		T	
Ethyl Benzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Etriyi Borizorio	- 0000 mg/kg ( Kat )	- 10-100 mg/kg ( Kabbit )	- 17.2 mg/L ( Nat ) + n
100-41-4			
1100 41 4			

### Information on toxicological effects

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

our onregornerty				
Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Ethylene Glycol Butyl Ether 111-76-2	A3	Group 3	-	-
Ethyl Benzene 100-41-4	А3	Group 2B	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

**Chronic toxicity** Ethylbenzene has been classified by the International Agency for Research on Cancer

(IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated

overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver

effects.

Target Organ Effects blood, Central nervous system, Eyes, Hematopoietic System, kidney, liver, lungs,

Respiratory system, Skin.

**Aspiration hazard** No information available.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

# 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

#### **Ecotoxicity**

47.26% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Acetone	-	4.74 - 6.33: 96 h Oncorhynchus	10294 - 17704: 48 h Daphnia
67-64-1		mykiss mL/L LC50 6210 - 8120: 96	magna mg/L EC50 Static 12600 -
		h Pimephales promelas mg/L LC50	12700: 48 h Daphnia magna mg/L
		static 8300: 96 h Lepomis	EC50
		macrochirus mg/L LC50	
Solvent Naphtha, Medium Aliphatic	450: 96 h Pseudokirchneriella	800: 96 h Pimephales promelas	100: 48 h Daphnia magna mg/L
64742-88-7	subcapitata mg/L EC50	mg/L LC50 static	EC50
Ethylene Glycol Butyl Ether	-	1490: 96 h Lepomis macrochirus	1000: 48 h Daphnia magna mg/L
111-76-2		mg/L LC50 static 2950: 96 h	EC50 1698 - 1940: 24 h Daphnia
		Lepomis macrochirus mg/L LC50	magna mg/L EC50

Ethyl Benzene	4.6: 72 h Pseudokirchneriella	11.0 - 18.0: 96 h Oncorhynchus	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 438: 96 h	mykiss mg/L LC50 static 4.2: 96 h	EC50
	Pseudokirchneriella subcapitata	Oncorhynchus mykiss mg/L LC50	
	mg/L EC50 2.6 - 11.3: 72 h	semi-static 7.55 - 11: 96 h	
	Pseudokirchneriella subcapitata	Pimephales promelas mg/L LC50	
	mg/L EC50 static 1.7 - 7.6: 96 h	flow-through 32: 96 h Lepomis	
	Pseudokirchneriella subcapitata	macrochirus mg/L LC50 static 9.1 -	
	mg/L EC50 static	15.6: 96 h Pimephales promelas	
		mg/L LC50 static 9.6: 96 h Poecilia	
		reticulata mg/L LC50 static	

# Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Acetone 67-64-1	-0.24
Propane 74-98-6	2.3
Butane 106-97-8	2.89
Ethylene Glycol Butyl Ether 111-76-2	0.81
Ethyl Benzene 100-41-4	3.118

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number U002 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1	-	Included in waste stream: F039	-	U002
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Ethyl Benzene	Toxic
100-41-4	Ignitable

# **14. TRANSPORT INFORMATION**

DOT

UN/ID no. UN1950
Proper shipping name Aerosols
Hazard Class 2.1

#### **TP275SP CASE POWER TAN LF**

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to DOT.

Description UN1950, Aerosols, 2.1

**Emergency Response Guide** 126

Number

**TDG** 

UN/ID no. UN1950 Proper shipping name Aerosols **Hazard Class** 

Description UN1950, Aerosols, 2.1

MEX

UN/ID no. UN1950 Proper shipping name Aerosols

**Hazard Class** 

UN1950, Aerosols, 2 Description

ICAO (air)

UN/ID no. UN1950 Aerosols Proper shipping name **Hazard Class** 2.1 **Special Provisions** A145, A167

Description UN1950, Aerosols, 2.1

IATA

UN/ID no. UN1950

Aerosols, flammable Proper shipping name

**Hazard Class** 2.1 **ERG Code** 10L

**Special Provisions** A145, A167, A802

UN1950, Aerosols, flammable, 2.1 Description

**IMDG** 

UN/ID no. UN1950 Proper shipping name Aerosols **Hazard Class** EmS-No. F-D, S-U

**Special Provisions** 63,190, 277, 327, 344, 959 Description UN1950, Aerosols, 2

RID

UN/ID no. UN1950 Proper shipping name Aerosols **Hazard Class** 2.1 Classification code 5F

**Description** UN1950, Aerosols, 2.1

ADR

UN/ID no. UN1950 Proper shipping name Aerosols Hazard Class 2.1 Classification code 5F **Tunnel restriction code** (D)

**Special Provisions** 190, 327, 344, 625

**Description** UN1950, Aerosols, 2.1, (D)

Labels 2.1

ADN

Proper shipping name Aerosols **Hazard Class** 2.1 Classification code

190, 327, 344, 625 **Special Provisions** 

**Description** UN1950, Aerosols, 2.1

Hazard label(s) 2.1 Limited quantity (LQ) 1 L

Ventilation VE01, VE04

# 15. REGULATORY INFORMATION

#### **International Inventories**

Complies **TSCA DSL/NDSL** Complies \* **EINECS/ELINCS** Does not comply \* Does not comply \* **ENCS IECSC** Complies \* **KECL** Does not comply \* **PICCS** Does not comply \* **AICS** Does not comply \*

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

# **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
Ethylene Glycol Butyl Ether - 111-76-2	1.0	
Ethyl Benzene - 100-41-4	0.1	

#### SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethyl Benzene 100-41-4	1000 lb	X	X	Х

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
Ethyl Benzene	1000 lb	=	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

### **US State Regulations**

<sup>\*</sup> This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	Х	X	X
Solvent Naphtha, Medium Aliphatic 64742-88-7	Х	-	-
Propane 74-98-6	X	X	X
Butane 106-97-8	X	X	X
Stoddard Solvent 8052-41-3	Х	X	Х
Titanium dioxide 13463-67-7	Х	X	Х
Ethylene Glycol Butyl Ether 111-76-2	Х	X	Х
Xylene 1330-20-7	Х	Х	Х
Propylene Glycol Methyl Ether 107-98-2	Х	Х	Х
Ethyl Benzene 100-41-4	Х	Х	Х
Manganese Dioxide 1313-13-9	X	-	Х
Crystalline Silica 14808-60-7	Х	X	Х

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

### Hazardous air pollutants (HAPS) content

This product contains no reportable Hazardous Air Pollutants

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 4 Instability 0 Physical and Chemical Properties \*

Health hazards 2 \* Flammability 4 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend \*= Chronic Health Hazard

**Revision Date** 19-Jun-2015

**Revision Note** 

No information available

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet